


TECHNICAL DATA

5627A | Precision Thermometer, RTD Temperature Probe



Key features

- Temperature range up to 420 °C.
- Accuracy of up to ± 0.025 °C.
- NVLAP-accredited calibration.
- Three different length options, with both six- and nine-inch models covering a temperature range of -200 °C to 300 °C.

Product overview: 5627A | Precision Thermometer, RTD Temperature Probe

One of the best features of this RTD sensor is that it conforms to the standard 385 curve, letting you use your DIN/IEC RTD meters fully. Why use a precision thermometer or RTD temperature probe that's less accurate than your meter?

The 5627A is manufactured using a coil suspension element design for increased shock and vibration resistance. It has a mineral-insulated sheath with a minimum bend radius of 19 mm (3/4-inch) for flexibility and durability. (Bend, if any, should be specified at time of order.)

Six- and nine-inch 5627A precision thermometers are calibrated at -196 °C, -38 °C, 0 °C, 200 °C, and 300 °C. For 12-inch versions of these precision thermometers, the point at 300 °C is replaced by a calibration point at 420 °C.

Each probe is individually calibrated and includes an accredited report of calibration from the manufacturer.

This RTD temperature probe is an excellent value for a precision thermometer. It has the price-to-accuracy and price-to-durability ratios you should demand in all of the precision thermometers you buy!

Specifications: 5627A | Precision Thermometer, RTD Temperature Probe

Specifications	
Resistance	Nominal 100 Ω
Temperature Coefficient	0.00385 $\Omega/\Omega/^\circ\text{C}$ nominal
Temperature Range	-200 $^\circ\text{C}$ to 420 $^\circ\text{C}$ (5627A-6 and 5627A-9 to 300 $^\circ\text{C}$; transition and cable temperature: 0 $^\circ\text{C}$ to 150 $^\circ\text{C}$)
Drift Rate (k=2)	$\pm 0.04^\circ\text{C}$ at 0 $^\circ\text{C}$ after 100 hours at 420 $^\circ\text{C}$
Sheath Material	316 Stainless Steel
Leads	PTFE-insulated, nickel-plated stranded copper, 22 AWG
Termination	Specify. See Ordering Information.
Time Constant	Four seconds maximum for 63.2 % response to step change in water moving at 3 fps.
Bending Radius	Sheath may be ordered with a bend on a minimum radius of 19 mm (3/4 in) except for 50 mm (2 in) area of sheath near tip. (Fluke lab requires 20 cm [8 in] of unbent sheath to re-calibrate.)
Calibration	Includes manufacturer's accredited calibration and table with R vs. T values in 1 $^\circ\text{C}$ increments from -196 $^\circ\text{C}$ to 420 $^\circ\text{C}$ (to 300 $^\circ\text{C}$ for 5627A-6 and 5627A-9). ITS-90 coefficients included.
Immersion	At least 100 mm (4 in) recommended
Calibrated Accuracy† (k=2)	$\pm 0.026^\circ\text{C}$ at -196 $^\circ\text{C}$ $\pm 0.046^\circ\text{C}$ at 0 $^\circ\text{C}$ $\pm 0.077^\circ\text{C}$ at 200 $^\circ\text{C}$ $\pm 0.124^\circ\text{C}$ at 420 $^\circ\text{C}$
Size	5627A-12: 305 mm x 6.35 mm (12 in x 1/4 in) 5627A-9: 229 mm x 4.7 mm (9 in x 3/16 in) 5627A-6: 152 mm x 4.7 mm (6 in x 3/16 in)
†Includes calibration uncertainty and 100 hr drift.	

Ordering information



5627A RTD

5627A Precision Thermometer, RTD Temperature Probe

Part#: 0

5627A-6-X

Secondary PRT, 152 mm x 4.7 mm (6 x 3/16 in), -200 °C to 300 °C

Part#: 0

(17025 accredited calibration included. Traceable to NIST standards.)

X = termination. Specify "A" (INFO-CON for 914X), "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs).

5627A-9-X

Secondary PRT, 229 mm x 4.7 mm (9 x 3/16 in), -200 °C to 300 °C

Part#: 0

(17025 accredited calibration included. Traceable to NIST standards.)

X = termination. Specify "A" (INFO-CON for 914X), "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs).

5627A-12-X

Secondary PRT, 305 mm x 6.35 mm (12 x 1/4 in), -200 °C to 420 °C

Part#: 0

(17025 accredited calibration included. Traceable to NIST standards.)

X = termination. Specify "A" (INFO-CON for 914X), "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs).

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2026 Fluke Corporation.
Specifications subject to change without notice.
10/2026

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**