

TECHNICAL DATA

Type S and Type R Thermocouples 5649/5650



Key features

- Type S and R Thermocouples.
- Platinum and platinum-rhodium alloy.
- Temperature range of 0 °C to 1450 °C.
- Uncertainties as good as 0.15 °C over most of that range.
- Calibrated at four fixed points (Sn, Zn, Al, Ag) and then extrapolated to 1450 °C.
- Four version available, 20 and 25 inch lengths with and without CJC.

Product overview: Type S and Type R Thermocouples 5649/5650

The measuring junction of both the 5649 and the 5650 thermocouples is encased in a 0.25-inch (6.35 mm) alumina sheath that can be ordered in lengths of 20 or 25 inches (50.8 or 63.5 cm) to fit the specific requirements of your application. A reference, or "cold," junction may also be ordered. The reference junction uses a stainless steel sheath and is 8.25 inches long (21 cm) by 0.188 inches in diameter (4.8 mm). The thin diameter minimizes the immersion depth needed, but the extra length ensures you can get all the immersion you like.

Special tin-plated, solid-copper connecting wires with ultra-low EMF properties are used to help retain the integrity of your thermocouple measurement junction where the probe attaches to your micro voltmeter or Hart Black Stack.

Each thermocouple probe comes with an individual calibration with fixed-point standards to reduce uncertainties to 0.12 °C to 0.37 °C from 232 °C to 962 °C and 0.37 °C to 2.5 °C, increasing linearly >962 °C to 1450 °C (extrapolated).

The probe assembly can be easily disassembled for performing your own bare-wire calibrations.

Specifications: Type S and Type R Thermocouples 5649/5650

Specifications	
Range	0 °C to 1450 °C
Type	Platinum/13 % Rhodium vs. platinum (type R) Platinum/10 % Rhodium vs. platinum (type S)
Calibration	Calibration Uncertainty (k=2, 95%): 232 °C to 962 °C 0.12 °C to 0.37 °C >962 °C to 1450 °C (extrapolated): 0.37 °C to 2.5 °C, increasing linearly
Hot Junction Sheath Dimensions	6.35 mm (0.25 in) diameter; see Ordering Information for lengths
Reference Junction Sheath Dimensions	4.8 mm dia. x 210 mm long (0.188 x 8.25 in)
Long-Term Stability	± 0.5 °C to 1100 °C ± 2.0 °C to 1450 °C (over one year depending on usage)
Short-Term Stabilities	± 0.2 °C to 1100 °C ± 0.6 °C to 1450 °C
Immersion	At least 152 mm (6 in) recommended
Protective Case	Model 2609 case included
Weight	1 kg (2 lb)

Ordering information



5649 / 5650 R/S

Type R and Type S Thermocouple Standards

Part#: 0

5649-20-X

Type R TC, 508 mm (20 in)

Part#: 0

X = termination. Specify "B" (bare wire), "W" (generic copper-to-copper TC connector), or "R" (standard Type R/S TC connector). Models with reference junctions should not specify "R" and models without reference junctions should not specify "W".

5649-20CX

Type R TC, 508 mm (20 in), with reference junction

Part#: 0

X = termination. Specify "B" (bare wire), "W" (generic copper-to-copper TC connector), or "R" (standard Type R/S TC connector). Models with reference junctions should not specify "R" and models without reference junctions should not specify "W".

5649-25-X

Type R TC, 635 mm (25 in)

Part#: 0

X = termination. Specify "B" (bare wire), "W" (generic copper-to-copper TC connector), or "R" (standard Type R/S TC connector). Models with reference junctions should not specify "R" and models without reference junctions should not specify "W".

5649-25CX

Type R TC, 635 mm (25 in), with reference junction

Part#: 0

X = termination. Specify "B" (bare wire), "W" (generic copper-to-copper TC connector), or "R" (standard Type R/S TC connector). Models with reference junctions should not specify "R" and models without reference junctions should not specify "W".

5650-20-X

Type S TC, 508 mm (20 in)

Part#: 0

X = termination. Specify "B" (bare wire), "W" (generic copper-to-copper TC connector), or "R" (standard Type R/S TC connector). Models with reference junctions should not specify "R" and models without reference junctions should not specify "W".

5650-20CX

Type S TC, 508 mm (20 in), with reference junction

Part#: 0

X = termination. Specify "B" (bare wire), "W" (generic copper-to-copper TC connector), or "R" (standard Type R/S TC connector). Models with reference junctions should not specify "R" and models without reference junctions should not specify "W".

5650-25-X

Type S TC, 635 mm (25 in)

Part#: 0

X = termination. Specify "B" (bare wire), "W" (generic copper-to-copper TC connector), or "R" (standard Type R/S TC connector). Models with reference junctions should not specify "R" and models without reference junctions should not specify "W".

5650-25CX

Type S TC, 635 mm (25 in), with reference junction

Part#: 0

X = termination. Specify "B" (bare wire), "W" (generic copper-to-copper TC connector), or "R" (standard Type R/S TC connector). Models with reference junctions should not specify "R" and models without reference junctions should not specify "W".

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2026 Fluke Corporation.
Specifications subject to change without notice.
10/2026

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**